

# Flexcon® DrumCal™ for GHS compliant labeling

The Globally Harmonized System (GHS) of Classification and Labeling of Chemicals enables better hazard communication regarding chemicals to all persons who are potentially exposed by standardizing the information to be communicated on container labels. It also enables ready availability of information on the hazardous properties of such chemicals and recommended control measures should an accident happen.

Meet GHS standards with confidence and ease.

## Applications

- Painted metal, plastic, and fiber drums
- Ground and maritime shipping
- End user in-plant labeling

## Options to meet your needs

- High-performance adhesives for cold temperature environments and better chemical resistance
- General-purpose adhesive for less demanding applications
- BS 5609 compliant products

## Polyester

- Superior chemical resistance
- Thermal transfer and laser\* printable
- 2-year outdoor durability

## Vinyl

- Excellent chemical resistance
- Laser\* printable
- 2-year outdoor durability

\*Dry- and liquid-toner based laser systems

GHS requires that manufacturers and end users include specific information on all primary and secondary labels.

1. Product identifiers
2. Signal words
3. Hazard statements
4. Precautionary statements
5. Supplier identification
6. Pictograms created with a combination of red and black ink

The basic parts of a GHS compliant label:



Contact your sales representative for more information.

# Flexcon® DrumCal™ for GHS compliant labeling

DrumCal™ product		21023	21043	41028	41048	41743
FLX#		000325	000327	000332	000612	069117
BS 5609 Recognition (Section 2)		●	●	●	●	●
BS 5609 Recognition (Section 3) - multiple ribbons		●	●			
Film	Polyester	●	●			
	Vinyl			●	●	●
Liner	77 lb. roll to sheet	●	●			●
	92 lb. roll to sheet			●	●	
Print Technology	Thermal transfer	●	●			●
	Laser (with press applied varnish)			●	●	
	Laser (topcoated)	●	●			●
Adhesive	High performance		●		●	●
	General purpose	●		●		
Cold temperature applications			●	●	●	●
Superior chemical resistance		●		●	●	
Outdoor durability (years)		2	2	2	2	2
Availability	Master width	54"	54"	54"	54"	54"
	Quick Ship			●		●
	Samples			●		●

**Product Performance and Suitability**

Descriptive information, performance data, and recommendations for Flexcon products are guides and not specifications. Providing this information is to assist you and does not constitute a warranty of any kind by Flexcon.

Purchasers must independently determine the material's suitability for their intended use. No distributor, salesperson, or representative of Flexcon is authorized to provide any warranty or guarantee beyond what is stated. FLEXCON MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, COURSE OF PERFORMANCE, OR TRADE USAGE.